



TYPICAL DELINEATOR INSTALLATION

NOTE:
 DELINEATORS SHOULD BE PLACED AT A CONSTANT DISTANCE FROM THE ROADWAY EDGE EXCEPT THAT, WHEN AN OBSTRUCTION EXISTS NEAR THE PAVEMENT EDGE, THE LINE OF DELINEATORS MAKES A SMOOTH TRANSITION TO THE INSIDE OF THE OBSTRUCTION.

SPACING FOR ROAD EDGE DELINEATORS				
RADIUS OF CURVE M	SPACING ON CURVE M	SPACING IN ADVANCE & BEYOND CURVE		
		1ST. M	2ND. M	3RD. M
15	6	12	20	38
46	9	18	27	55
61	11	21	34	66
76	12	26	38	76
91	15	29	44	88
122	17	34	52	91
152	20	38	58	91
183	21	43	64	91
213	23	46	70	91
244	24	50	75	91
274	26	53	79	91
305	27	56	84	91

EFFECTIVE DATE: OCTOBER 1997

COMMONWEALTH OF PUERTO RICO
 DEPARTMENT OF TRANSPORTATION
 AND PUBLIC WORKS
 HIGHWAY AND TRANSPORTATION AUTHORITY

RECOMMENDED BY: *[Signature]*
 ASST. EXC. DIR. FOR TRAFFIC
 DATE: *2 Oct 97*

APPROVED BY: *[Signature]*
 EXECUTIVE DIRECTOR
 DATE: *Oct 9 97*

APPROVED BY: *[Signature]*
 DIV. ADM. FHWA-PR DIVISION
 DATE: *Oct 9 97*

DATE	REVISION	BY

DELINEATORS
 TYPICAL APPLICATION
 TYPES 1, 2, 3 & 4

STD. DWG. DLN 2 OF 2