



GENERAL NOTE:

1. FOR ORIENTATION OF SIGNS SEE ORIENTATION DETAILS.
2. VERTICAL CLEARANCE TO BOTTOM OF LOWEST SIGN PANEL SHALL BE 2.130 (7'-0") TO 2.500 (7'-6") FROM THE FINISH GRADE OF THE NEAREST LANE EDGE.
3. THE OFFSET SHALL BE MEASURED FROM THE EDGE OF THE NEAREST LANE TO THE EDGE OF THE NEAREST POST, EXCEPT IN THE CASE OF GUARDRAIL IN WHICH CASE THE OFFSET SHALL BE MEASURED FROM THE BACK OF THE GUARDRAIL POST TO THE NEAREST EDGE OF PANEL.

EFFECTIVE DATE: JULY 2000

COMMONWEALTH OF PUERTO RICO DEPARTMENT OF TRANSPORTATION AND PUBLIC WORKS HIGHWAY AND TRANSPORTATION AUTHORITY		RECOMMENDED BY: DEPUTY EXEC. DIR. FOR TRAFFIC AND TOLL ROADS DATE: 11-V-00	APPROVED BY: EXECUTIVE DIRECTOR DATE: MAY-19-00
GROUND MOUNTED BREAK-AWAY SIGNS OFFSET DRAWINGS HIGHWAYS WITH MINIMAL RIGHT OF WAY		DATE	BY
07-1999	ADD NOTE	IV.	IV.
03-2000	REVISED NOTE 2		
STD.	DWG.	GMTS	5 OF 15